

Specifications for Laydown Machine

<i>Weight</i>	<i>15,000 lbs. +/- 1000 lbs.</i>
<i>Hitch Type</i>	<i>2 5/16 Gooseneck</i>
<i>Maximum Length</i>	<i>46' - 8"</i>
<i>Deck Length</i>	<i>39'</i>
<i>Deck Height</i>	<i>42"</i>
<i>Maximum Height (Stability Jacks Fully Extended)</i>	<i>54"</i>
<i>Tubular Indexers</i>	<i>Able to reach down 18"</i>
<i>Fuel Gauge</i>	<i>On Fuel Tank</i>
<i>Block Heater</i>	<i>Yes</i>
<i>Operator Controls</i>	<i>Hydro Electric mounted on unit & with Wireless Activated Remote Control</i>
<i>Trigger</i>	<i>3600 lbs.</i>
<i>Maximum Lifting Capacity</i>	<i>39' - 49' with extension.</i>
<i>Trough Length</i>	<i>25 sec @ 2000 RPM</i>
<i>Trough Cycle Time</i>	<i>32.5 degree "V" w/ 10 ft. Bolt on Trough extension</i>
<i>Trough Style</i>	<i>2 Left, 2 Right</i>
<i>Tubular Trough Kickers</i>	<i>3600 lbs.</i>
<i>Maximum Lifting Capacity</i>	<i>9 ft. to 23 ft. to 27 ft. w/ext.</i>
<i>Adjustable Trough Heights</i>	<i>4 - 12" stroke cylinders</i>
<i>Stability Jacks</i>	<i>Parker SOL 48 to 60 G.P.M, 3000 psi Max</i>
<i>Hydraulic Pump</i>	<i>40 US Gal.</i>
<i>Hydraulic Tank</i>	<i>Chain Type</i>
<i>Skate</i>	<i>Cummins B3.3T-P74S</i>
<i>Engine</i>	<i>74 hp @ 2600 RPM</i>
<i>Horsepower</i>	<i>40 US Gal.</i>
<i>Fuel Capacity</i>	

